

USER MANUAL

REFRIGERATOR FREEZER

For Home Use Only

GR-RS905WIA-PGY(67)



TOSHIBA

CONTENTS

- 1. Safety warnings1
- 2. Proper use of the freezer8
- 3. Structure and functions12
- 4. Maintenance and care of the refrigerator.....18
- 5. Trouble shooting26
- 6. Disposal of your appliance27

Dear user :

- Thank you very much for purchasing this Toshiba product.
- Read this user manual and become completely familiar with the product before. use in order to use this product safely and correctly.
- Keep this user manual in a handy place for future reference.
- Make sure that you received your warranty.

1. Safety warnings

READ SAFETY PRECAUTIONS BEFORE INSTALLATION

To prevent injury to the user or other people and property damage, the following instructions must be followed. Incorrect operation due to ignoring of instructions may cause harm or damage.

1.1 Warning

WARNING



Warning: risk of fire / flammable materials

- **WARNING: Risk of fire disaster and explosion**
The refrigerant of the appliance is flammable, please be care not to damage the cooling pipes during installation and transportation. if gas leakage happens, please contact the distributor or local service agent, and the following precautions should be always taken:
 1. Open the windows for ensuring good ventilation.
 2. No fire around and please do not use other electric appliance.
- This appliance is intended to be used in household and similar applications such as staff kitchen areas in shops, offices and other working environments; farm houses and by clients in hotels, motels and other residential type environments; bed and breakfast type environments; catering and similar non-retail applications.
- Children should be supervised to ensure that they do not play with the appliance.
- **WARNING: Risk of fire disaster and electric shock**
The power cord should be replaced when it has been damaged. please contact the distributor or local service agent for replacement.
- Please unplug the power plug from socket when clean the appliance or leave the appliance nonuse for a long time.
- Do not use extension cord or ungrounded (two prong) adapters.
- **WARNING: Keep ventilation openings, in the appliance enclosure or in the built-in structure, clear of obstruction.**
- **WARNING: Do not use mechanical devices or other means to accelerate the defrosting process, other than those recommended by the manufacturer.**
- **WARNING: Do not damage the refrigerant circuit.**
- **WARNING: Do not use electrical appliances inside the food storage compartments of the appliance, unless they are of the type recommended by the manufacturer.**

-
- **WARNING:** Please abandon the refrigerator according to local regulators for its use of flammable cyclopentane foaming material and refrigerant.
 - **WARNING:** When positioning the appliance, ensure the supply cord is not trapped or damaged.
 - **WARNING:** Do not locate multiple portable socket-outlets or portable power supplies at the rear of the appliance.
 - **WARNING:** Please fill with potable water only. Please do not fill with hot water or liquids other than potable water such as juices.
 - **DANGER:** Risk of child entrapment. Before you throw away your old refrigerator or freezer:
 - Take out the doors.
 - Leave the shelves in place so that children may not easily climb inside.
 - The refrigerator must be disconnected from the source of electrical supply before attempting the installation of accessory.
 - Refrigerant and cyclopentane foaming material used for the refrigerator are flammable. Therefore, when the refrigerator is scrapped, it shall be kept away from any fire source and be recovered by a special recovering company with corresponding qualification other than be disposed by combustion, so as to prevent damage to the environment or any other harm.
 - For IEC standard: This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.
 - For EN standard: This appliance can be used by children aged from 8 years and above and persons with reduced physical sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.
 - Please do not use the appliance on traffic means (such as ship and so on).
 - If noise, odor and smoking happens, please unplug the power plug immediately, and contact the distributor or local service agent.
 - Please do not put your hands under or behind the appliance to prevent from being hurt.

-
- Please leave the packing materials and other parts out of the reach of children to prevent from risk of suffocation.
 - To avoid contamination of food, please respect the following instructions:
 - Opening the door for long periods can cause a significant increase of the temperature in the compartments of the appliance.
 - Clean regularly surfaces that can come in contact with food and accessible drainage systems.
 - Clean water tanks if they have not been used for 48h, flush the water system connected to a water supply if water has not been drawn for 5days. (note 1)
 - Store raw meat and fish in suitable containers in the refrigerator, so that it is not in contact with or drip onto other food.
 - Two-star frozen-food compartments are suitable for storing pre-frozen food, storing or making ice-cream and making ice cubes. (note 2)
 - One-, two- and three star compartments are not suitable for the freezing of fresh food. (note 3)
 - For appliances without a 4-star compartment: this refrigerating appliance is not suitable for freezing foodstuffs. (note 4)
 - If the refrigerating appliance is left empty for long periods, switch off, defrost, clean, dry, and leave the door open to prevent mouldy developing within the appliance.
 - Note 1,2,3: Please confirm whether it is applicable according to your product compartment type.
 - For a freestanding appliance: this refrigerating appliance is not intended to be used as a built in appliance.
 - Any replacement or maintenance of the LED lamps is intended to be made by the manufacturer, its service agent or similar qualified person.
 - This product contains a light source of energy efficiency class (***).

1.2 Meaning of safety warning symbols



Prohibition symbol

This is a prohibition symbol.

Any in compliance with instructions marked with this symbol may result in damage to the product or endanger the personal safety of the user.



Mandatory symbol

This is a mandatory symbol.

It is required to operate in strict observance of instructions marked with this symbol; or otherwise damage to the product or personal injury may be caused.




Cautioning symbol

This is a cautioning symbol.


Instructions marked with this symbol require special caution. Insufficient caution may result in slight or moderate injury, or damage to the product.

This manual contains lots of important safety information which shall be observed by the users.


1.3 Electricity related warnings




- Do not pull the power cord when pulling the power plug of the refrigerator. Please firmly grasp the plug and pull out it from the socket directly.
- To ensure safe use, do not damage the power cord or use the power cord when it is damaged or worn.



- Please do not touch the power plug with wet hand to prevent from electric shock.
- Please use a dedicated power socket and the power socket shall not be shared with other electrical appliances. The power plug should be firmly contacted with the socket or else fires might be caused.




- Please ensure that the grounding electrode of the power socket is equipped with a reliable grounding line.
- Please ask for help from persons with professional qualification to examine whether the socket is with reliable grounding line or not.
- It is the end-consumers' responsibility to change the ungrounded socket into grounded socket.




- Please turn off the valve of the leaking gas and then open the doors and windows in case of leakage of gas and other flammable gases. Do not unplug the refrigerator and other electrical appliances considering that spark may cause a fire.
- Do not use electrical appliances on the top of the appliance, unless they are of the type recommended by the manufacturer.


1.4 Warnings for using



- Do not arbitrarily disassemble or reconstruct the refrigerator, nor damage the refrigerant circuit; maintenance of the appliance must be conducted by a specialist.
- Damaged power cord must be replaced by the manufacturer, its maintenance department or related professionals in order to avoid danger.






- The gaps between refrigerator doors and between doors and refrigerator body are small, be noted not to put your hand in these areas to prevent from squeezing the finger. Please be gentle when close the refrigerator door to avoid falling articles.



- Do not pick foods or containers with wet hands in the freezing chamber when the refrigerator is running, especially metal containers in order to avoid frostbite.
- Do not allow any child to get into or climb the refrigerator; otherwise suffocation or falling injury of the child may be caused.
- Please do not put heavy or dangerous objects on top of the appliance (bottles, tableware, or something containing liquid).

1.5 Warnings for placement



- Do not put flammable, explosive, volatile and highly corrosive items in the refrigerator to prevent damages to the product or fire accidents.
- Do not place flammable items near the refrigerator to avoid fires.
- The refrigerator is intended for household use, such as storage of foods; it shall not be used for other purposes, such as storage of blood, drugs or biological products, etc.
- Do not store beer, beverage or other fluid contained in bottles or enclosed containers in the freezing chamber of the refrigerator ; or otherwise the bottles or enclosed containers may crack due to freezing to cause damages.

1.6 Warnings for energy

- Refrigerating appliances might not operate consistently (possibility of defrosting of contents or temperature becoming too warm in the frozen food compartment) when sited for an extended period of time below the cold end of the range of temperatures for which the refrigerating appliance is designed.
- The fact that effervescent drinks should not be stored in food freezer compartments or cabinets or in low-temperature compartments or cabinets, and that some products such as water ices should not be consumed too cold.
- The need to not exceed the storage time(s) recommended by the food manufacturers for any kind of food and particularly for commercially quick-frozen food in food-freezer and frozen-food storage compartments or cabinets.
- The precautions necessary to prevent an undue rise in the temperature of the frozen food while defrosting the refrigerating appliance, such as wrapping the frozen food in several layers of newspaper.
- The fact that a rise in temperature of the frozen food during manual defrosting, maintenance or cleaning could shorten the storage life.
- The necessity that, for doors or lids fitted with locks and keys, the keys be kept out of the reach of children and not in the vicinity of the refrigerating appliance, in order to prevent children from being locked inside.

1.7 Warnings for disposal








- Refrigerant and cyclopentane foaming material used for the refrigerator are flammable. Therefore, when the refrigerator is scrapped, it shall be kept away from any fire source and be recovered by a special recovering company with corresponding qualification other than be disposed by combustion, so as to prevent damage to the environment or any other harm.



- When the refrigerator is scrapped, disassemble the doors, and remove gasket of door and shelves; put the doors and shelves in a proper place, so as to prevent trapping of any child.

2. Proper use of the freezer

2.1 Placement



- Before the refrigerator is moved, take all objects inside out, fix the glass partitions, vegetable holder, freezing chamber drawers and etc. with tape, and tighten the leveling feet; close the doors and seal them with tape. During moving, the appliance shall not be laid upside down or horizontally, or be vibrated; the inclination during movement shall be no more than 45° .
- Before use, remove all packing materials, including button cushions, foam pads and tapes inside of the refrigerator; tear off the protective film on the doors and the refrigerator body. Keep away from heat and avoid direct sunlight. Do not place the freezer in moist or watery places to prevent rust or reduction of insulating effect.
- Do not spray or wash the refrigerator; do not put the refrigerator in moist places easy to be splashed with water so as not to affect the electrical insulation properties of the refrigerator.
- The refrigerator is placed in a well-ventilated indoor place; the ground shall be flat, and sturdy (rotate left or right to adjust the wheel for leveling if unstable).
- The top space of the refrigerator shall be greater than 30cm, and the refrigerator should be placed against a wall with a free distance more than 10cm to facilitate heat dissipation.



Precautions before installation:

Before installation or adjusting of accessories, it shall be ensured that the refrigerator is disconnected from power. Precautions shall be taken to prevent fall of the handle from causing any personal injury.

2.2 Leveling feet

1. Precautions before operation:


Before operation of accessories, it shall be ensured that the refrigerator is disconnected from power.

2. Schematic diagram of the levelling feet:

Before adjusting the leveling feet, precautions shall be taken to prevent any personal injury.

3. Adjusting procedures:

- Turn the feet clockwise to raise the refrigerator;
- Turn the feet counterclockwise to lower the refrigerator;
- Adjust the right and left feet based on the procedures above to a horizontal level.



(The picture above is only for reference. The actual configuration will depend on the physical product or statement by the distributor)


2.3 Leveling door

1. Precautions before operation:

Before operation of accessories, it shall be ensured that the refrigerator is disconnected from power.

Before adjusting the door, precautions shall be taken to prevent any personal injury.

2. Schematic diagram of leveling the door body



(The picture above is only for reference. The actual configuration will depend on the physical product or statement by the distributor)

Adjusting procedures:

1) When the fridge door is low :


Open the door, use a wrench to loosen the locking nut and to rotate the adjusting nut anti-clockwise to raise the height of the door. Once the doors are aligned, then tighten the locking nut by rotating it anti-clockwise.

2) When the fridge door is high :


Open the door, use a wrench to rotate the adjusting nut clockwise to lower the height of the door. Once the doors are aligned, then tighten the locking nut by rotating it anti-clockwise.

2.4 Changing the Light


Any replacement or maintenance of the LED lamps is intended to be made by the manufacturer, its service agent or similar qualified person.



2.5 Starting



- Before initial start, keep the refrigerator still for half an hour before connecting it to power supply.
- Before putting any fresh or frozen foods, the refrigerator shall have run for 2-3 hours, or for above 4 hours in summer when the ambient temperature is high.
- Spare enough space for convenient opening of the doors and drawers or statement by the distributor.




2.6 Energy saving tips

- The appliance should be located in the coolest area of the room, away from heat producing appliances or heating ducts, and out of the direct sunlight.
- Let hot foods cool to room temperature before placing in the appliance. Overloading the appliance forces the compressor to run longer. Foods that freeze too slowly may lose quality, or spoil.
- Be sure to wrap foods properly, and wipe containers dry before placing them in the appliance. This cuts down on frost build-up inside the appliance.
- Appliance storage bin should not be lined with aluminum foil, wax paper, or paper toweling. Liners interfere with cold air circulation, making the appliance less efficient.
- Organize and label food to reduce door openings and extended searches. Remove as many items as needed at one time, and close the door as soon as possible.

3. Structure and functions

3.1 Key components



(The picture above is only for reference. The actual configuration will depend on the physical product or statement by the distributor)

Refrigerating chamber

- The Refrigerating chamber is suitable for storage of a variety of fruits, vegetables, beverages and other food consumed in the short term, suggested storage time 3days to 5 days.
- Cooking foods shall not be put in the refrigerating chamber until cooled to room temperature.
- Foods are recommended to be sealed up before putting into the refrigerator.
- The glass shelves can be adjusted up or down for a reasonable amount of storage space and easy use.


Freezing chamber

- The low temperature freezing chamber may keep food fresh for a long time and it is mainly used to store frozen foods and making ice.
- The freezing chamber is suitable for storage of meat, fish, rice balls and other foods not to be consumed in short term.
- Chunks of meat are preferably to be divided into small pieces for easy access. Please be noted food shall be consumed within the shelf time.

Drawers, food boxes, shelves, etc. placed according to the position in the picture above are the most energy efficient.

Note: Storage of too much food during operation after the initial refrigerator. Foods stored shall not block the air outlet; or otherwise the freezing effect will also be adversely affected.

3.2 Functions



1. Display

- 1) Wireless network icon 2) Temperature display area 3) Super Cool icon
4) Super Frz icon

2. Buttons

- A Fridge button B Freezer button C Cubed Ice button
D Half Ice button E Pure Air Turbo button

3. Display

- a. The first time the refrigerator is powered on, the screen will be bright for three seconds, accompanied by a power-on sound, then it will enter normal operation display; (The initial set temperatures for the fridge and freezer compartments upon initial power-on are 5°C and -20°C respectively).
- b. When a snag happens, it presents the snag code (in a cycle display mode). In anormal state, the fridge’s set temperature instead of a snag code is shown.

4. Setting of the temperature of the fridge

Press the "Fridge" button to adjust the temperature of fridge compartment. The setting range of the fridge compartment is 2°C-8°C; automatic locking takes effect after 10 seconds.

Press the "Fridge" button 3s to enter the Super Cool function.

5. Setting of the temperature of the freezer

Press the "Freezer" button to adjust the temperature of freezer compartment. The setting range of the freezer compartment is -24 - -16°C; automatic locking takes effect after 10 seconds. Press the "Freezer" button 3s to enter the Super Frz function.

6. Ice maker setting

Short press:

Press the "Cubed Ice" button to adjust the cubed ice maker switch. When the cubed ice maker is on, the "On" icon next to the button of the cubed ice maker lights up, and vice versa "Off".

Press the "Half Cube" button to adjust the half ice maker switch. When the half ice machine is on, the "On" icon next to the half ice machine button lights up, and vice versa "Off".

7. Setting of the mode

Press the "Fridge" button 3s to set/exit the Super Cool mode;

When setting the Super Cool mode, the temperature of the fridge is set for 2°C automatically. When existing the Super Cool mode, the temperature will return to that set before the Super Cool mode. (Adjusting the fridge gear in the Super Cool mode will exit the Super Cool mode)

Press the "Freezer" button 3s to set/exit the Super Frz mode;

When setting the Super Frz mode, the temperature of the freezer is set for -24°C automatically. When existing the Super Frz mode, the temperature will return to that set before the Super Frz mode. (Adjusting the freezing gear in the Super Frz mode will exit the Super Frz mode).

8. Pure Air Turbo mode

Press the "PureAIR Turbo" button shortly to turn on the Pure Air Turbo function, and the Pure Air Turbo icon will light up.

9. Setting of wireless network

After the refrigerator powers on, "AP" will be shown in the temperature area on the display control panel when the user holds down the "PureAIR Turbo" button for 4 seconds. It means the wireless network is accessible. The user can log in TSmartLife App and connect the refrigerator with the wireless network according to the app's guidance. The sign "📶" will brighten when the connection is done. For the download of TSmartLifeApp and the way of connecting with the wireless network, please refer to the appendixes.

10. Notification of errors


The following notifications on the screen means malfunctions of the refrigerator.

Fault code	Fault name	Fault entry	Fault treatment
E1	Fault of the fridge's temperature sensor	The temperature shown on the sensor < -50°C, or the temperature shown on the sensor > +60°C.	Start and stop the cooling of the fridge alternately.
E2	Fault of the freezer's temperature sensor	The temperature shown on the sensor < -50°C, or the temperature shown on the sensor > +60°C.	Start and stop the freezing of the freezer alternately.
E5	Fault of the freezer's defrosting sensor	The temperature shown on the sensor < -50°C, or the temperature shown on the sensor > +60°C.	Stop the heater on time during defrosting.
E6	Communication fault	Failing to communicate 8s after the refrigerator is electrified or after the refrigerator has worked for one minute.	Operate the master control board according to its setting before the fault happens.
E7	Fault of the environmental temperature	The temperature shown on the sensor < -30°C, or the temperature shown on the sensor > +65°C.	Execute considering the environmental temperature is 25°C.
EH	Fault of the humidity sensor	Detected humidity < 5%RH or it > 105%RH (no alarm after 3 min)	Environmental temperature = 85% of humidity
Eh	Fault of the humidity control sensor	Detected humidity < 5%RH or it > 105%RH (no alarm after 3 min)	Control according to moderate humidity
CA	Failure of communication between main board and ice-making board	Failing to communicate 8s after the refrigerator is electrified or after the refrigerator has worked for one minute.	Ice maker not making ice
L8	Half Ice maker fault	Abnormal initialization of the half ice maker to find zero position	Ice maker not making ice
H8	Cubed ice maker fault	Abnormal initialization of the cubed ice maker to find zero position	Ice maker not making ice
L7	Sensor fault in the ice cube tray of half Ice maker	The actual resistance value is > 1034KΩ, or the resistance value is < 484Ω to report an error, directly short circuit or open circuit to report an error. (allowable error)	Ice maker not making ice
H7	Sensor fault in the ice cube tray of cubed ice maker	The actual resistance value is > 1034KΩ, or the resistance value is < 484Ω to report an error, directly short circuit or open circuit to report an error. (allowable error)	Ice maker not making ice
L9	Half Ice maker off-ice fault	Half Ice maker off-ice fault	Try to freeze again
H9	Cubed ice maker off-ice fault	Cubed ice maker off-ice fault	Try to freeze again

4. Maintenance and care of the refrigerator

4.1 Overall cleaning

- Dusts behind the refrigerator and on the ground shall be timely cleaned to improve the cooling effect and energy saving.
- Check the door gasket regularly to make sure there are no debris. Clean the door gasket with a soft cloth dampened with soapy water or diluted detergent.
- The interior of the refrigerator should be cleaned regularly to avoid odor.
- Please turn off the power before cleaning interior, remove all foods, drinks, shelves, drawers, etc.
- Use a soft cloth or sponge to clean the inside of the refrigerator, with two tablespoons of baking soda and a quart of warm water. Then rinse with water and wipe clean. After cleaning, open the door and let it dry naturally before turning on the power.
- For areas that are difficult to clean in the refrigerator (such as narrow sandwiches, gaps or corners), it is recommended to wipe them regularly with a soft rag, soft brush, etc. and when necessary, combined with some auxiliary tools (such as thin sticks) to ensure no contaminants or bacterial accumulation in these areas.
- Do not use soap, detergent, scrub powder, spray cleaner, etc. as these may cause odors in the interior of the refrigerator or contaminated food.
- Clean the bottle frame, shelves and drawers with a soft cloth dampened with soapy water or diluted detergent. Dry with a soft cloth or dry naturally.
- Wipe the outer surface of the refrigerator with a soft cloth dampened with soapy water, detergent, etc., and then wipe dry.
- Do not use hard brushes, clean steel balls, wire brushes, abrasives (such as toothpastes), organic solvents (such as alcohol, acetone, banana oil, etc.), boiling water, acid or alkaline items, which may damage the fridge surface and interior. Boiling water and organic solvents such as benzene may deform or damage plastic parts.
- Do not rinse directly with water or other liquids during cleaning to avoid short circuits or affect electrical insulation after immersion.






Please unplug the refrigerator for defrost and cleaning.



4.2 Cleaning of door tray

- According to the direction arrow in the figure below, use both hands to squeeze the tray, and push it upward, then you can take it out.
- After washing the tray having been taken out, you can adjust its installing height in accordance with your requirement.



4.3 Cleaning of Glass shelf

- As the innermost part of the refrigerator liner where contacting the shelves has a backstop, you shall raise the shelves upward, then you can be able to take it out.
- Adjust or clean the shelves according to your requirement. Soft towels or sponge dipped in water and non-corrosive neutral detergents are suggested for cleaning. The freezer of shall be finally cleaned with clean water and dry cloth. Open the door for natural drying before the power is turned on. Do not use hard brushes, clean steel balls, wire brushes, abrasives, such as toothpastes, organic solvents (such as alcohol, acetone, banana oil, etc.), boiling water, acid or alkaline items clean refrigerator considering that this may damage the fridge surface and interior.



(The picture above is only for reference. The actual configuration will depend on the physical product or statement by the distributor)

4.4 Defrosting

- The refrigerator is made based on the air-cooling principle and thus has automatic defrosting function. Frost formed due to change of season or temperature may also be manually removed by disconnection of the appliance from power supply or by wiping with a dry towel.

4.5 Out of operation

- Power failure: In case of power failure, even if it is in summer, foods inside the appliance can be kept for several hours; during the power failure, the times of door opening shall be reduced, and no more fresh food shall be put into the appliance.
- Long-time nonuse: The appliance shall be unplugged and then cleaned; then the doors are left open to prevent odor.
- Moving: Before the refrigerator is moved, take all objects inside out, fix the glass partitions, vegetable holder, freezing chamber drawers and etc. with tape, and tighten the leveling feet; close the doors and fix them with tape. During moving, the appliance shall not be laid upside down or horizontally, or be vibrated; the inclination during movement shall be no more than 45°.



**The appliance shall run continuously once it is started.
Generally, the operation of the appliance shall not be interrupted; otherwise the service life may be impaired.**




4.6 Precautions for the use of ice maker

1. Instructions for using and adding water to the water tank of ice make

- Water source: bottled purified water or potable water.
- Water adding steps:


a) When lifting and sliding the water tank of the ice maker out of the refrigerator, stop at the point where there is a noticeable resistance.

It is not recommended to take out the water tank and add water.




It is recommended to open the lid at the place and add water


b) Open the water filling cover.




c) Bottled water or potable water shall not exceed the maximum water level mark MAX-4L or be lower than the minimum water level mark MIN.



d) Close the water filling cover.



e) Insert the protrusion at the bottom of the water tank into the groove of the water tank bracket, ensuring that the water tank of the ice maker is pushed to the correct position.



NOTE:


Drinks, hot water, coffee, etc. are not allowed to be added to the water tank of ice maker.

- When disassembling the water tank used in the ice maker, a small amount of water will spill onto the glass shelf. When water spills, wipe dry with a soft cloth.
- Drinks, hot water, coffee, etc. are not allowed to be added to the water tank of ice maker. It may cause system failure and water leakage.
- Please clean the water tank before use.
- Do not remove the water tank bracket or damage the water pipe. It may cause system failure and water leakage.
- Discard the drained water (about 5 cups) and ice (about 30 pieces) from the first use. It may contain impurities.
- Ensure that the water outlet of the ice maker water tank and the inlet of the water tank bracket are fully inserted. Incomplete insertion may cause system failure or water leakage.
- If the water supply system of the ice maker is not used for 2 -3 days, discard the ice in first use, which may have smell or dust.
- If you do not use the ice maker system for about 2 weeks, discard the water in the water tank. The water in the water tank may have been contaminated.
- It is recommended that you supplement appropriate purified water to the water tank of ice maker within about 2 days. The purified water can also be added to the water tank of ice maker according to the actual amount of ice cubes used. The water volume shall be kept within the normal range, not exceeding the maximum level MAX and not lower than the minimum level MIN.


2. Notes for use of ice maker

- Ice making time and ice storage capacity
Generally, each ice making time is 100min.
For cubed ice cubes, 100g ice can be made each time, about 10 ice cubes.
For half Ice cubes, 68g ice can be made each time, about 18 ice cubes.
(The ambient temperature is 25°C and the door is not opened or closed).
For cubed ice cubes, it takes approximately 18-22 fills to reach full capacity, resulting in around 180-220 ice cubes
For half Ice cubes, it takes approximately 26-31 fills to reach full capacity, resulting in around 450-530 ice cubes. It is normal for a few small ice cubes to adhere to each other.
- **The ice making time may be extended in the following situations**
Freezing chamber is not fully cooled at the beginning of use.
The temperature is low in winter or the ambient temperature is high in summer.
The door is opened and closed more times; or more food is put in at one time.
The space around the refrigerator is too narrow.
- **Notes for ice making**
The ice detection rod of this ice maker will continue to make ice before touching the ice; when the ice detection rod touches the ice in the ice storage box, the ice making process stops. At this time, ice storage box is full of ice.
- **The following situation may prevent the ice from being made even though there is water in the water tank:**

a) Foreign matters other than ice cubes in the ice storage box contact the detection rod.




b) Foreign matters other than ice cubes in the ice storage box cause collision or ice making grid is overturned.



- **The following situation may reduce the amount of ice made:**

Some ice cubes piling up in some areas may hit the detection rod too early, leading to ice making being stopped when ice making is insufficient.



To solve this problem, please avoid storing other items in the ice storage box and stack the ice cubes evenly in ice storage box.

4.7 Use and cleaning of ice storage box

The ice in the ice storage box may be lumped or the outlet may be blocked for other reasons. In such cases, the ice storage container needs to be cleaned or to remove the blockage.

If the ice cubes are not used for a long time or the ice storage boxes are not used for a long time, they need to be cleaned out. The specific steps are as follows:

- 1) Pull out the drawer.
- 2) Lift and take out the Ice storage box.



When taking ice, first pull out the drawer, then take out the Ice storage box, do not take out the Ice storage box directly

Warning :

- When using the ice maker, do not put anything other than ice cubes in the ice storage box. Putting something other than ice will cause collision damage or ice making stop when the ice making grid is overturned.
- If you need to store other items in the ice storage box, please stop using the ice making function.
- When the ice making function is enabled again, please remove other items in the ice storage box and clean the ice storage box.
- When putting other items into the ice storage box, please be careful of high items to avoid jamming the ice maker.
- If not used for a long time, the ice cubes in the ice storage box, ice maker, should be discarded.

-
- Be sure to use a soft wet cloth or sponge for cleaning, and rinse the parts to be rinsed with clean water. (To avoid mold, water rust, etc.) Do not use the following items: detergent, bleach, abrasive powder, brush, diluent, gasoline, etc. (Otherwise, peculiar smell or malfunction may be caused.)
 - Do not disassemble, modify, or repair the automatic ice maker in the freezer by yourself.
 - Do not touch the ice making part of the automatic ice maker with your hands (upper side of the ice-making box.)

5. Trouble shooting

- You may try to solve the following simple problems by yourself. If them cannot be solved, please contact the after-sales department.

Occurrence	Possible cause/inspection items
Failed operation	Check whether the appliance is connected to power or whether the plug is in well contact Check whether the voltage is too low Check whether there is a power failure or partial circuits have tripped
Odor	Odorous foods shall be tightly wrapped Check whether there is any rotten food Clean the inside of the refrigerator
Long-time operation of the compressor	Long operation of the refrigerator is normal in summer when the ambient temperature is high It is not suggestible having too much food in the appliance at the same time Food shall get cool before being put into the appliance The doors are opened too frequently
Light fails to get lit	Check whether the refrigerator is connected to power supply and whether the illuminating light is damaged Have the light replaced by a specialist
Doors cannot be properly closed	The door is stuck by food packages Too much food is placed The refrigerator is tilted
Loud noise	Check whether the floor is level and whether the refrigerator is placed stably Check whether accessories are placed at proper locations
Door seal fails to be tight	Remove foreign matters on the door seal Heat the door seal and then cool it for restoration (or blow it with an electrical drier or use a hot towel for heating)
Water pan overflows	There is too much food in the chamber or food stored contains too much water,resulting in heavy defrosting The doors are not closed properly, resulting in frosting due to entry of air and increased water due to defrosting
Hot housing	Heat dissipation of the built-in condenser via the housing, which is normal When housing becomes hot due to high ambient temperature, storage of too much food or shutdown of the compressor is shut down, provide sound ventilation to facilitate heat dissipation
Surface condensation	Condensation on the exterior surface and door seals of the refrigerator is normal when the ambient humidity is too high. Just wipe the condensate with a clean towel
Abnormal noise	Buzz: The compressor may produce buzzes during operation, and the buzzes are loud particularly upon start or stop. This is normal. Creak: Refrigerant flowing inside of the appliance may produce creak, which is normal

6. Disposal of your appliance



Correct Disposal of this product:

This marking indicates that this product should not be disposed with other household wastes throughout the EU. To prevent possible harm to the environment or human health from uncontrolled waste disposal, recycle it responsibly to promote the sustainable reuse of material resources. To return your used device, please use the return and collection systems or contact the retailer where the product was purchased. They can take this product for environmental safe recycling.

AMBIENT TEMPERATURE

This appliance is designed to operate in ambient temperature specified by its category marked on the rating plate.

Climate category	Ambient temperature (from...to...)
SN	+10°C to +32°C
N	+16°C to +32°C
ST	+16°C to +38°C
T	+16°C to +43°C

#DetailsMatter

Hefei Hualing Co., Ltd.
No.176 JinXiu Road, Hefei Economy & Technology Development Area, 230601,
Hefei, Anhui, P.R. China
MADE IN CHINA

<https://www.toshiba-lifestyle.com/sg/>