Products Information Data Sheet

These products are hermetically sealed state in a vessel, and are exempted from Safety Data Sheet regulations. However, this manual provides you with referential information to safety use the products.

Section 1 - Products and Company Identification

| Products name | : | Carbon Zinc Batteries (Primary Battery) |
|----------------|---|--|
| Products sizes | : | R20, R14, R6, R03, R1, 6F22 |
| Company | : | TOSHIBA LIFESTYLE PRODUCTS & SERVICES CORPORATION |
| Address | : | 1310 Omiya-cho, Saiwai-ku, Kawasaki, Kanagawa 212-0014, Japan |
| Telephone | : | +81-44-577-0142 |
| Fax | : | +81-44-576-6025 |
| | | |

Section 2 - Hazards Identification

| GHS Classification | : | Not applicable |
|--------------------|---|---|
| Toxicity | : | When the electrolyte leaked from the cell/battery adheres to the skin, it may cause damage to the skin. In addition, When it is gotten in the eyes, it may cause damage to the eyes such as losing sight. |
| Hazard | : | There is a risk of explosion if cells/batteries are thrown into fire or heated. When stacking or jumbling cells/batteries may cause heat generation and explosion by external short circuits. |

Section 3 - Composition/ Information on Ingredients

| Ingredients | CAS# | PRTR | Weight/Content |
|--|------------|---------------|----------------|
| Manganese dioxide (MnO ₂) | 1313-13-9 | 1-412 | 17~35wt% |
| Acetylene black (C) | 1333-86-4 | Not regulated | 3~15wt% |
| Zinc chloride (ZnCl ₂) | 7646-85-7 | 1-1 | 2~10wt% |
| Ammonium chloride (NH ₄ Cl) | 12125-02-9 | Not regulated | 0~10wt% |
| Zinc (Zn) | 7440-66-6 | Not regulated | 10~40wt% |
| Lead (Pb) | 7439-92-1 | 1-304 | 0.05~0.15wt% |

Section 4 - First Aid Measures (In case of electrolyte leakage from the battery)

| Inhalation of electrolyte fume | : | If a person inhaled steam, move to the place where air is fresh immediately. If you feel unwell, immediately seek medical attention. |
|--------------------------------|---|---|
| Skin contact by electrolyte | : | If the content adheres to skin, immediately wash it with a large amount of clean water and soap promptly. If you have pain, immediately seek medical attention. |
| Eyes contact by electrolyte | : | If the content enters eyes, rinse eyes with a large amount of clean water for more than 15 minutes, and immediately seek medical attention. |
| Ingestion of electrolyte | : | If a cell/battery is swallowed, immediately seek medical attention. |

Section 5 - Fire Fighting Measures

| Fire extinguishers | : | Powder extinguisher, foam extinguisher, carbon dioxide gas |
|--------------------|---|--|
| | | extinguisher, large amount of dry sand |

| Specific firefighting method | : | In the initial state of a fire, move cells/batteries from near the fire source, to a safe location. At that time, work at a windward location, as far as possible, and be sure to wear the protective equipment. (fireproof gloves, protective mask, protective eyewear, protective clothing) |
|--------------------------------------|---|---|
| Protection of firefighting personnel | : | Be wear protective equipment (fireproof gloves, protective mask, protective eyewear, protective clothing) for the keeping safe. (If possible, use atmosphere-supplying respirator) |

Section 6 - Accidental Removing Measures

<u>The cell/battery hermetically contains constituents in a vessel, so contents normally may not leak out.</u> However, if the contents leaks because of a mechanical or electrical stress, wipe with liquid-boric to absorb it, and collect in a vessel. After that, flush the site with a large amount of water. At that time, be sure to wear protective gloves and protective eyewear.

| tion 7 - Handling and Sto | lage | |
|---|------------|---|
| Handling | : | Do not solder a cell/battery body. Do not contact cell/battery terminals between each other, of with another conductor. Do not throws into fire, disassemble heat, dent, deform, charge nor drop a battery. Do not dip cell/battery in water or seawater. |
| Storage | : | Store cells/batteries without direct sunlight, high temperature high humidity, rain, dew, etc., and select a storage location with a temperature as low as possible (preferable temperature 10-25°C and relative humidity 70% or less). In addition, kee cells away from dangerous matter such as combustible of ignitable materials. Absolutely never place a cell/battery contact with a combustible or conductive substance. Prepar appropriate firefighting equipment. |
| Note | | |
| Note | : | See handling and storing precautions described in the produc catalog, specification, etc. |
| tion 8 - Exposure Control | : Is/Pe | catalog, specification, etc. ersonal Protection |
| tion 8 - Exposure Control Protection of respiratory | : Is/Pe | catalog, specification, etc. |
| tion 8 - Exposure Control | : Is/Pe | catalog, specification, etc. ersonal Protection |
| tion 8 - Exposure Control Protection of respiratory organs | : Is/Pe | catalog, specification, etc. ersonal Protection Not required in a normal operating state |
| tion 8 - Exposure Control Protection of respiratory organs Protection of eyes | : | catalog, specification, etc. ersonal Protection Not required in a normal operating state Not required in a normal operating state Not required in a normal operating state |
| tion 8 - Exposure Control Protection of respiratory organs Protection of eyes Other protective tools etc. | : | catalog, specification, etc. ersonal Protection Not required in a normal operating state Not required in a normal operating state Not required in a normal operating state al Properties Cylindrical. |
| tion 8 - Exposure Control Protection of respiratory organs Protection of eyes Other protective tools etc. tion 9 - Physical and Che Shape | : | catalog, specification, etc. ersonal Protection Not required in a normal operating state Not required in a normal operating state Not required in a normal operating state al Properties Cylindrical. Contents are sealed in a stiff stainless steel vessel. |
| tion 8 - Exposure Control Protection of respiratory organs Protection of eyes Other protective tools etc. tion 9 - Physical and Che Shape PH | : | catalog, specification, etc. ersonal Protection Not required in a normal operating state Not required in a normal operating state Not required in a normal operating state al Properties Cylindrical. Contents are sealed in a stiff stainless steel vessel. Not applicable because a cell is not soluble with water. |
| tion 8 - Exposure Control Protection of respiratory organs Protection of eyes Other protective tools etc. tion 9 - Physical and Che Shape PH Boiling point/boiling range | : | catalog, specification, etc. ersonal Protection Not required in a normal operating state Not required in a normal operating state Not required in a normal operating state al Properties Cylindrical. Contents are sealed in a stiff stainless steel vessel. Not applicable because a cell is not soluble with water. No information |
| tion 8 - Exposure Control Protection of respiratory organs Protection of eyes Other protective tools etc. tion 9 - Physical and Che Shape PH Boiling point/boiling range Melting point | : | catalog, specification, etc. ersonal Protection Not required in a normal operating state Not required in a normal operating state Not required in a normal operating state al Properties Cylindrical. Contents are sealed in a stiff stainless steel vessel. Not applicable because a cell is not soluble with water. No information No information |
| tion 8 - Exposure Control Protection of respiratory organs Protection of eyes Other protective tools etc. tion 9 - Physical and Che Shape PH Boiling point/boiling range | : | catalog, specification, etc. ersonal Protection Not required in a normal operating state Not required in a normal operating state Not required in a normal operating state al Properties Cylindrical. Contents are sealed in a stiff stainless steel vessel. Not applicable because a cell is not soluble with water. No information |

Section 10 - Stability and Reactivity

If a number of cells/batteries are jumbled without insulating terminals, they may short and possibly electrolyte leakage, generate heat, and rupture. When the cell/battery is charged, the electrolytic solution or the like may suddenly spurt out due to the generation of gas from the inside of the cell/battery. There is also the possibility of rupture. If the cell/battery is heated or thrown into a fire, it may explode and splash the electrolyte. If the cell/battery is disassembled, it may short and possibly electrolyte leakage, generate heat, and rupture.

Section 11 - Toxicological Information

There is no toxicity because chemical substances are hermetically sealed in a metal vessel.

Section 12 - Ecological Information

No information as the cells/batteries.

Section 13 - Disposal Considerations

Disposal of the substance should be done according to the laws and regulations.

Although used cells/batteries can be discarded basically as "Non burnable rubbish" some local governments sort and collect them at their own discretion. Therefore, observe instructions of the government you belong to, to dispose of the substance.

Keep the following discarding precautions :

- Even a used cell/battery sometimes stores electric energy. Therefore, to prevent the cell/battery from short-circuit, isolate cells/batteries from each other by a method such as taping +, terminals of cells/batteries, or using the individual housing case of a cell/battery
- Packing cells/batteries so that they are not shorted, and prevent the package from being wetted.
- If cells/batteries must be discarded in a country other than Japan, observe the instructions of the country and local government.
- The user as business entity must contract with a firm of disposing of industrial waste, and appropriately discard the substance.

Section 14 - Transportation Information

Handling :

When transporting cells/batteries, avoid high temperatures, high humidity and condensation. Pack the cell/battery so that it does not short-circuit, and fix it so that the load does not collapse. Cell/Batteries should be stored at room temperature (45 ° C or less: 10-25 ° C recommended) with low temperature changes and a relative humidity of 70% or less. Handle the container with care and do not subject it to shocks that could leave dents in the cell/battery.

UN Number and UN Class : Not applicable (<u>Not Dangerous Goods</u>)

Section 15 - Regulatory Information

The laws and ordinances about the cell/battery shall obey the latest laws and ordinances.

- EU Battery Directive (2006/66/EC, 2013/56/EU) (Europe)
- Regulation (EC)No.1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals (REACH) (Europe)
- Act on Preventing Environmental Pollution of Mercury (Japan)

Section 16 - Other Information

The cells/batteries fall in the category of "Article" defined by EPA (U.S. Environment Protection Agency), and chemical substances used in a battery satisfy the application exemption conditions as part of "Article," so the batteries are not regulated by TSCA.

Please take appropriate measures according to individual conditions, uses, and usages before using. In addition, the contents of this description were created based on the materials and information available to us at the time of creation, and may be revised to new information.

Preparation This Sheet

:

TOSHIBA LIFESTYLE PRODUCTS & SERVICES CORPORATION Engineering Group Planning & Procurement Dept. Battery Business Div.